



Proven to reduce 99.98% of SARS-CoV-2 virus (the virus that causes COVID-19) on surfaces within 7 hours.¹

THE TECHNOLOGY

The Aerus[®] Mid-Range Blaster utilizes ActivePure Technology and provides 24/7 air purification and surface decontamination in large indoor spaces up to 5,000 sq. ft. (464 m²) while the unit is running. It has been proven to reduce up to 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in “The Proof” section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as a complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure[®] Technology has been proven to significantly reduce the following contaminants and pathogens¹:

- SARS-CoV-2
- *Staphylococcus aureus*
- *Aspergillus niger* endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- *Bacillus globigii*
- MS2 Bacteriophage
- *Staphylococcus epidermidis*
- PhiX-174
- *Erwinia herbicola*
- *Listeria monocytogenes*
- Murine Norovirus
- *E. coli*
- *Candida auris*
- *Botrytis cinerea*
- *Sclerotinia sclerotiorum*
- *Legionella pneumophila*
- *Aspergillus versicolor*
- *Clostridium difficile*
- *Salmonella enterica*

THE BENEFITS

The Aerus Mid-Range Blaster provides 24/7 air purification and surface decontamination in indoor spaces up to 5,000 sq. ft. while the unit is running. It is a proactive and effective solution for your home or business.

- Uses ActivePure Technology, proven to reduce up to 99.9% of many common types of bacteria, viruses, and mold in indoor air and surfaces¹
- Reduces VOC gases, smoke, and odors without the use of ozone¹
- Portable unit is easy to move for versatility



Inducted into the 2017 Space
Technology Hall of Fame by
the Space Foundation

Assembled in USA



¹View test results at
Aerusonline.com/Scientific-Proof



MID-RANGE BLASTER



Product Information 00667; Model F213A
Meets California Ozone Emissions Limit. CARB Certified.
Validated to UL 2998

Technology Included ActivePure® Technology - (4) 9" Cells

Electrical Input Voltage: 120V
Power Consumption: 172W

Mechanical Fuse: 2.25A; 2.0A slowblow
Airflow Rate: 300 CFM

Safety Conforms to UL 507

Weight & Dimensions 24 lbs (10.9 kg) (unpackaged)
22" H x 13" W x 13" D (48.26 cm x 33.02 cm x 33.02 cm)

Sound Level 57.4 dB(A)

Coverage¹ Up to 5,000 sq. ft. (464 m²) depending on occupant density and other factors.
For commercial applications involving high density occupancy, max coverage is up to 2,500 sq. ft. (232 m²) with 8' ceilings.

Warranty Limited 3 year warranty



Contact Name: _____



Email: _____



Phone Number: _____

1. Recommended ceiling height to not exceed 10 ft. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, other layers of protection. Testing actual application results before and after utilization of the technology, in as near as possible identical conditions, is a recommended measure to optimize effective deployment.