



Air You Can Trust™



Features ActivePure® Technology, proven to reduce up to 99.9% of many common types of bacteria, viruses, and mold¹

THE TECHNOLOGY

The Sanctuary Mini allows you to retrofit your mini-split HVAC system with ActivePure Technology. Patented ActivePure Technology is an advanced air and surface purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as a complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens¹:

- SARS-CoV-2
- *Staphylococcus Aureus*
- *Aspergillus niger endospores*
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- *Bacillus globigii*
- MS2 Bacteriophage
- *Staphylococcus epidermidis*
- PhiX-174
- *Erwinia Herbicola*
- *Listeria monocytogenes*
- Murine Norovirus
- *E. coli*
- *Candida auris*
- *Botrytis cinerea*
- *Sclerotinia sclerotiorum*
- *Legionella pneumophila*
- *Aspergillus versicolor*
- *Clostridium difficile*
- *Salmonella enterica*

THE BENEFITS

The Sanctuary Mini provides 24/7 air purification and surface decontamination in indoor spaces up to 500 sq. ft. while the mini-split HVAC system is running. It is a proactive and effective solution for your home or business.

- Uses ActivePure Technology, proven to reduce up to 99.9% of many common types of bacteria, viruses, and mold in indoor air and surfaces¹
- Reduces VOC gases, smoke and odors¹
- Quickly works to clean the indoor environment
- Discreet or concealed installation, attaches easily to mini-split HVAC systems
- Requires only 17 watts of electricity



¹View test results at Aeronline.com/Scientific-Proof



Inducted into the 2017 Space Technology Hall of Fame by the Space Foundation Assembled in USA

SANCTUARY MINI

SPECIFICATIONS

Product Information	00671 Model: A1019C This unit does not meet California requirements and cannot be shipped to California.
Technology Included	ActivePure® Technology - (1) Bulb Assembly w/ 5" Bulb
Electrical	Input Voltage: 120VAC, 230VAC Current: 0.38A @ 120VAC Power Factor: 0.99 Power: 20 Watts Max
Mechanical	Air Exchange: Distribution via air handler
Weight & Dimensions	0.39 lbs (6.24 oz) 4.3" L x 6.7" W x 3.1" H (10.92 cm L x 17.02 cm W x 7.87 cm H)
Operating Temperature	23°F - 131°F (-5°C - 55°C)
Coverage¹	Up to 500 sq. ft. (46.4 m ²) depending on occupant density and other factors ¹ .
Warranty	Limited 2 year warranty



Contact Name: _____



Email: _____



Phone Number: _____

1. Recommended ceiling height to not exceed 10 ft. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, and other layers of protection